



Planar CarbonLight CLM Series

Mesh LED Displays

6.9 & 10.4mm pixel pitchesSee-through mesh designCarbon fiber constructionIP65 outdoor protection rating



Planar® CarbonLight™ CLM Series see-through, lightweight mesh LED video wall displays are designed for indoor or outdoor environents and feature high transparency and low wind resistance for unique viewing experiences. Thin and modular design paired with high-strength carbon fiber casing fits a wide range of simple or complex hanging or free-standing applications.

Carbon Fiber Strength

Planar CarbonLight LED display solutions share a patented carbon fiber construction that makes them uniquely lightweight, thin and strong. Their refined mechanical construction and innovative features enable fast and versatile installations that support creativity and catch the eye.



Product Highlights





Weatherproof

The lightweight displays feature an IP65 Ingress Protection Rating which means they are dust tight and protected against even powerful water jets. The mesh design lets wind pass through, making it an exciting option for outdoor events.

Quick-service Bracketry

Planar CarbonLight bracketry accommodates fast servicing and enables displays to be removed and installed at any location in the video wall without disrupting the overall layout.

Specifications

Model	CLM6.9	CLM10.4	
Pixel Pitch (mm)	6.9	10.4	
Resolution	72 x 144	96 x 96	
Cabinet Size (WxHxD)	500 x 1,000 x 45mm	500 x 1,000 x 45mm 19.69 x 39.37 x 1.77in	
Cabinet Weight	4.8kg	4.8kg 10.6lbs	
Weight Bearing Capacity (per cabinet)	1,000kg**	1,000kg** 2,204lb**	
Power Supply	Dual		
Power Consumption, Max (watts)	300/Cabinet 6,00/m² 56/ft²		
Power Consumption, Typical (watts)	150/Cabinet 300/ m ² 28/sft ²		
Line Voltage	100-240V AC, 50/60Hz		
Brightness Max	5,000 cd/m ²		
Contrast Ratio	2,00	0:1	
LED Refresh Rate	3,000Hz	4,000Hz	
Color Temperature, Calibrated	6,500k		
Viewing Angle Horizontal, Vertical	140°, 140°		
Frame Rate	30~70Hz		
Grey Scale	14 bit		
Service Access	Rear		
Installation	Hanging, Standing		
Lifetime, Typical	75,000 hrs		
Environment	Indoor or Oudoor		
Protection Rating	IP65		
Operating Temp.	-20° to 40° C -4° to 104° F		
Storage Temp.	-20° to 50° C -4° to 122° F		
Cabinet Material	Carbon Fiber		
** Weight Rearing Canacity for hang	Vaight Rearing Canacity for hanging		

^{**} Weight Bearing Capacity for hanging