



# PXN2410

24" Full HD LCD monitor

The Planar® PXN2410 is a 24" Full HD LCD monitor with an ultra-thin bezel design, integrated speakers, multiple inputs and an ergonomic stand. It is a great fit for office or home environments. It uses IPS technology to deliver wide viewing angles with no color shift. It is flicker free and incorporates blue light reduction presets. The LED backlight reduces energy consumption.



SPECIFICATION	DETAIL
Product Name	PXN2410
Planar Part Number	998-2944-00
Viewable Size	23.8" diagonal (20.75" horizontal x 11.67" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and Vertical
Response Time (typ)	6 ms (GTG)
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	Full HD 1080P, 1920 x 1080
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2745 mm

<b>Refresh Rate</b>	48 to 76Hz (60 Hz recommended)
<b>Dimensions (W x H x D)</b>	24.2" x 20.5" x 9.1" (612.84 mm x 519.39 mm x 229.63 mm)
<b>Dimensions without Stand</b>	24.2" x 14.5" x 2.1" (612.84 mm x 367.46 mm x 52.3 mm)
<b>Panel Depth</b>	2.1" (52.3 mm)
<b>Display Weight</b>	10.8 lb/4.9kg (7.0 lb/ 3.145 kg without stand)
<b>Shipping weight</b>	13.3 lb (6.8 kg)
<b>Video Inputs</b>	HDMI®, DisplayPort, VGA
<b>HDCP</b>	Yes
<b>Audio Output</b>	Integrated 2W/channel stereo speakers, headphone jack
<b>External Connections</b>	HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out
<b>Compatibility</b>	PC and Mac® (adapter may be required for Mac)
<b>Power Supply</b>	Internal
<b>Power Consumption (max)</b>	14.7W Typical (<0.5W standby)
<b>Power Requirements</b>	AC 100/240 VAC
<b>Operating Temperature</b>	0° to +40°C (32° to 104°F)
<b>Humidity</b>	10 - 85% RH (non-condensing)
<b>Mount</b>	Built-in 100 mm VESA, back
<b>Product Approvals</b>	cTUVus, CE , FCC-B, RoHS
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US.
<b>Options / Features</b>	IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot ± 90°, Anti-glare coating ,Multi-language display, On screen display (OSD), Kensington® Security Slot
<b>Blue Light Reduction</b>	Yes
<b>Flicker Free</b>	Yes

<b>In the Box</b>	PXN2410 24" LED LCD Monitor, Power Cord, HDMI Cable, DisplayPort Cable, User's Guide
<b>UPC</b>	8 10689 00989 4
<b>HDMI®</b>	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/20/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*