



# Planar SLM652-T

4K LCD Touch Display

The Planar® Simplicity™ M Series SLM652-T is a 65" 4K LCD touch display for landscape or portrait interactive digital signage. It affordably incorporates media playback, cybersecurity mitigation, 4K @ 60Hz support, ENERGY STAR® efficiency and commercial functionality. Its elegant design with a narrow, logo-free bezel and slim profile provide the ideal interactive display for wayfinding, kiosks or digital signage in retail stores, education, medical offices, corporate meeting areas and hospitality.



| SPECIFICATION                   | DETAIL                             |
|---------------------------------|------------------------------------|
| Product Name                    | SLM652-T                           |
| Planar Part Number              | 998-3483-00                        |
| Protective Glass                | 2mm with AG coating                |
| Touch Technology                | Projected Capacitive: 20 points    |
| OS Compatibility                | Windows 10, 11, Mac OSX and Linux  |
| Display Resolution              | Ultra HD (3840 x 2160)             |
| Screen Size                     | 65 in. (diagonal)                  |
| Aspect Ratio                    | 16:9                               |
| Display Technology              | Direct-lit LED LCD                 |
| Display Active Area             | 56.5" x 31.9" (1434.3mm x 809.3mm) |
| Viewing Angle (typ)             | 178°                               |
| Backlight                       | LED                                |
| Backlight life (1/2 brightness) | 30,000 hrs (min)                   |
| Brightness (w/protective glass) | 400 nits                           |

|  |   |
|--|---|
| <b>Response Time (typ)</b>                         | 8 ms  |
| <b>Frame Rate</b>                                  | 60Hz  |
| <b>Contrast Ratio (typ)</b>                        | 1200:1  |
| <b>Pixel Pitch</b>                                 | 0.372mm x 0.372mm   |
| <b>Color Gamut</b>                                 | 72% NTSC  |
| <b>Display Color</b>                               | >1 billion colors. Full 10 bit data path  |
| <b>External Connections</b>                        | HDMI® x 2 (HDCP 2.2), USB-C x 1, VGA x 1, USB 3.0 x1, USB 2.0 x1, Media Player            |
| <b>Modes</b>                                       | 3840x2160 @ 24/25/30/60Hz; 480p, 576p, 720p @ 50/60 Hz; 1080p @ 50/60Hz; 1080i @ 50/60 Hz |
| <b>Display Control</b>                             | IR, RS-232, LAN, HDMI-CEC, Keypad   |
| <b>Cabinet Dimensions (W x H x D)</b>              | 58.0" x 33.2" x 2.5" (1473.3mm x 843.0mm x 62.8mm)  |
| <b>Cabinet Dimensions with Handles (W x H x D)</b> | Not Applicable  |
| <b>Orientation</b>                                 | Landscape/Portrait  |
| <b>Bezel Width</b>                                 | 0.8" (19.5mm)   |
| <b>Display Edge to Active Area</b>                 | 1.1" (26.7mm) CONFIRM   |
| <b>Weight</b>                                      | 63.9 lbs (29.0 kg)  |
| <b>Weight (Shipping)</b>                           | 82.0 lbs (37.2 kg)  |
| <b>Audio Input</b>                                 | PC Line In  |
| <b>Audio Output</b>                                | PC Line Out, S/PDIF   |
| <b>Speakers</b>                                    | 10W x 2 built-in  |
| <b>Enclosure</b>                                   | Metal rear enclosure  |
| <b>Mounting</b>                                    | VESA: 400mm x 400mm   |
| <b>Fanless</b>                                     | Yes   |
| <b>Line Voltage</b>                                | 100-240V; 50/60Hz   |
| <b>Power Consumption (typ)</b>                     | 130W (standby: <0.5W)   |
| <b>Operating Temperature</b>                       | 0° to +40°C (32° to 104°F) up to 3000m  |
| <b>Humidity</b>                                    | 20 - 85% RH (non-condensing)  |

|                               |   |
|-------------------------------|---|
| <b>Options / Features</b>     | USB playback, logo-free bezel, lockable rear keypad   |
| <b>Operating System</b>       | Proprietary OS based on Android 10.0. Google Play and third-party apps are not supported by Planar.   |
| <b>Storage</b>                | TBDGB (10.5GB available)  |
| <b>Approvals</b>              | FCC Class A, cTUVus, CE, RoHS, EN 303 645   |
| <b>ENERGY STAR® Certified</b> | Yes   |
| <b>Cyber Security</b>         | EN 303 645 certified  |
| <b>Security</b>               | No WiFi, Secure Shell (SSH) protocol, EN 303 645 certified  |
| <b>Warranty</b>               | 3 years   |
| <b>Recommended Usage</b>      | Up to 16 hours per day  |
| <b>In the Box</b>             | SLM652-T display, C14 connector US power cord - 1.8m, C14 connector EU power cord - 1.8m, HDMI cable - 1.8m, USB-C cable 1.8m, RS-232 cable, IR cable, USB A to B cable, remote control, cable clamps, 3mm tip passive stylus x1, Quick Start Guide |
| <b>UPC</b>                    | 8 10069 81099 7   |
| <b>HDMI®</b>                  | Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.                       |

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/8/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*