



RUNCO® CRYSTALSERIES™ CX-OPAL65 LCD

The Runco Crystal Series CX-OPAL65 LCD display with Optical Path ALignment (OPAL) technology is perfect for those who demand stellar image performance and a giant 65" diagonal image. Surrounded in an elegant black frame, the Runco CX-OPAL65 bespeaks luxury.



Native Resolution:	1920 x 1080
Screen Size:	CX-65HD = 65 in. (diagonal)
Screen Aspect Ratio:	16:9
Available Aspect Ratios:	4:3, Letterbox, 16:9, VirtualWide™
DTV Compatibility:	480i/p, 576i/p, 720p, 1080i, 1080p
ISF Settings:	Yes
Contrast Ratio:	CX-65HD = 2000:1
Data/Graphics Compatibility:	Refer to Table 7-2
Response Time (typical):	4.5 milliseconds
Vivix Processing:	3:2 or 2:2 pull down
Video/Audio Inputs:	Multiple input combinations with up to (2) Composite Video (1) S-Video (2) Component Video (4) HDMI 1.3a w/HDCP (1) RGB (15-pin D-sub) (5) Analog Audio (4 stereo RCA pairs + 3.5-mm stereo mini jack)
Control Inputs:	(1) RS-232 (9-pin D-sub) (1) Wired IR (3.5-mm mono mini jack)
Outputs:	(1) Digital Audio (S/PDIF optical) (1) Stereo Speakers
Audio System:	10W RMS x 2 Stereo Amplifier
Discrete IR Control:	Source, power and aspect ratios
Power Requirements:	100 to 240 VAC, 50/60Hz
Power Consumption (typical):	CX-65HD = 640 watts (2184.3 BTUs/hour); 8 watts in standby mode
Operating Environment:	40°F to 95°F (5°C to 35°C); 20% to 80% humidity (non-condensing); Altitude = 9,842 feet (3,000 meters)
Weight (including stand):	CX-65HD = 220.5 lbs. (100.00 kg)
Regulatory Approvals:	Complies with UL, FCC, CE, RoHS, C-Tick, NOM, GOST
Limited Warranty:	Two (2) years parts and labor from the date of delivery to the end user.

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.

Specifications are subject to change without notice. ©Copyright 2010 Runco International Inc. All rights reserved.