




# Planar PT3270Q

## 32" Touch Screen Monitor

The Planar® PT3270Q is a 32" interactive IPS LCD monitor with a 10-point touch screen and Quad HD resolution ideal for mounted applications. The big, bright, 10-bit panel provides 1.07 billion colors. The all glass front surface is anti-glare coated, reducing reflection, and is dust and water tight. It features a VESA 200 x 200 pattern for convenient mounting. A single USB-C cable delivers video, audio, and touch connectivity. The PT3270Q is perfect for retail and kiosk applications, enterprise IT, control rooms, and industrial environments.



SPECIFICATION	DETAIL
Product Name	PT3270Q
Planar Part Number	998-2949-00
Viewable Size	31.5" diagonal (27.5" horizontal x 15.5" vertical)
Touchscreen Type	Projected Capacitive
Number of Touch Points	10 points (Normal & Cover Glass), 2 points (Gloves), 1 point (WaterProof)
Touchscreen Interface	USB
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and Vertical
Response Time (typ)	14 ms (GTG)
Brightness (w/touchscreen)	297 cd/m <sup>2</sup> (typ.)
Brightness (w/o touchscreen)	350 cd/m <sup>2</sup> (typ.)
Display Type	IPS LCD with Edge-Lit LED Backlight

<b>Display Resolution</b>	2560 x 1440 WQHD
<b>Aspect Ratio</b>	16:9
<b>Palette</b>	1.07 billion colors
<b>Pixel Pitch</b>	0.2727 mm
<b>Refresh Rate</b>	49~76Hz (60Hz recommended)
<b>Panel Depth</b>	2.5" (64.6 mm)
<b>Dimensions (W x H x D)</b>	N/A - no stand included
<b>Dimensions (without stand)</b>	28.9" x 16.9" x 2.4" (734.8mm x 429.4 mm x 61.3 mm)
<b>Display Weight (w/o stand)</b>	28.0lb (12.7 kg)
<b>IP Rating</b>	IP65 (Front only)
<b>Shipping weight</b>	31.8 lb (14.4 kg)
<b>Video Inputs</b>	USB Type C (DisplayPort Alt Mode), DisplayPort,HDMI®
<b>HDCP</b>	Yes
<b>Audio Output</b>	5W x 2, earphone out
<b>Compatibility</b>	Windows® 11, 10, 8, 7, Linux
<b>External Connections</b>	USB Type C, HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out, USB 3.2 Gen 1 (Type A) x 2
<b>Power Supply</b>	Internal (AC)
<b>Power Requirements</b>	100 to 240 VAC 4.0A
<b>Power Consumption (max)</b>	26W typical (<0.5W standby)
<b>USB C Power Delivery</b>	N/A
<b>Operating Temperature</b>	5° to +40° C
<b>Mount</b>	Built-in 200 x 200 mm VESA, back
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US.

<b>Product Approvals</b>	UL/c-UL, FCC Class B, CE, UKCA, RoHS
<b>In the Box</b>	PT3270Q 32" Wide Touchscreen LED LCD Monitor, Power Cord, USB Cable (C to C), HDMI cable, DP cable, USB Cable (A to C), User's Guide
<b>UPC</b>	8 10689 00997 9
<b>Surface Treatment</b>	AG Coating

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/20/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*